

Heavy Aromatic/Solvesso

K-200 K-150 K-100

KAVEH Chemical's Solvesso offer high solvency and controlled evaporation characteristic that make them excellent for use in many industrial application such as additives, paint and coatings, pesticides, industrial cleaning, mastics and sealants and process fluids. They are available in three boiling ranges with varying Volatility.

The information in the product data sheets may be subject to change. For the most up-to-date datasheets please contact KAVEH Chemicals sales representative.

Property	Test Method	Unit	Typical Value		
Purity		wt%	>99	>99	>99
Color	ASTM D 1209	pt-Co	<10	<10	<20
Distillation range	ASTM D 1078	C°	157	180	191
Initial boiling point			167	187	220
50%			178	204	250
90%					
Flash point	ASTM D3278	C°	52	64	72
Specific Gravity	ASTM D-268	C°	0.86	0.897	0.95
			Solvesso K-100	Solvesso K-150	Solvesso K-200

Notes:

- Values indicated describe typical properties and do not constitute specification limits.
- The test methods specified above, or equivalent, will be used. Applicable sampling and testing methods are subject to change without notice and are available for review on request.
- This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of KAVEH Chemical as to the intended use.